


ProDVX White Bezel Screen Cover Installation Instructions

Follow these steps to install your new ProDVX **Tempered Glass Screen Cover** for ProDVX APPC 10 DSQ / DSK series.



Preparation and Cleaning:

The first and most important step to a perfect installation.

1. Choose a clean, well-lit environment with a flat surface.
2. Wash and dry your hands – Remove dirt and oils.
3. Clean your screen – Use alcohol or Screen / Glass cleaner in combination with microfiber cloth to clean off the entire screen.



4. Remove residual bits of dust with a mild adhesive. Dust is the most important thing to remove from under a screen protector: bubbles will eventually diffuse out through the plastic and tiny finger marks will probably merge with the glue, but dust specks stay. Lightly dab a sticky note (such as a "Post-it") all over the screen. Looking at the reflection of a bright area in the screen at an angle will confirm the presence or absence of dust.



V1.01 / 2018

Alignment:

Perfect alignment can be achieved by following these easy steps.

5. Take the Screen cover out of the protective sleeve




6. Peel off the protective film, please be careful the tempered glass is thin and when too much force is applied the Screen cover may break!
7. Do not touch the adhesive side once the protective layer is removed.
8. Slowly lower the uncovered adhesive side to your screen cover while carefully aligning it with the sides, bottom and active area of the LCD screen of your device. If it does not align perfectly, gently lift immediately and adjust until you are satisfied.



9. Once in place, lightly tap the center and slide your forefinger across the middle in the shape of a cross

V1.01 / 2018

Bubbles:
Easily eliminate bubbles.



10. Use your fingers and the microfiber cloth to firmly push bubbles out from the center towards the edges. If a bubble remains, press and hold it for five to ten seconds until it dissipates.

Finishing Touches: Last Step!

11. Use the microfiber cloth to polish your screen protector and you are ready to go!

Important Notes:

1. After installing, you may see faint wave patterns. This is quite common and is caused by the adhesive and bonding of the two glass surfaces together. This will disappear after 24-48 hours.
2. Although this product is made from tempered glass, please use caution by avoiding strong impact or bending.
3. Whether broken or intact, use caution when removing the screen protector from your device and keep out of the reach of children.
4. Please do not remove your screen protector for the purpose of re-installing it, **as it is a one-time use product**. Only remove the screen protector when discarding or replacing.

For further installation assistance, please contact our technical support: <http://prodvx.com/support>

